

Quectel EC20

Mini PCIe

Multi-mode LTE Module



Cat3
Max. 100Mbps(DL)
Max. 50Mbps(UL)



Max 42Mbps(DL)
Max 5.76Mbps(UL)



Mini PCIe Package



Embedded Abundant
Protocols



eCall



GLONASS+GPS



USB 2.0 High Speed
Compliant Interface



USB Drivers



Quectel Enhanced
AT Commands



EC20 Mini PCIe adopts the standard PCI Express® MiniCard form factor (miniPCIe) and provides global network coverage on the connectivity of LTE. It delivers 50Mbps-up and 100Mbps-down data rates on LTE FDD networks and can also be fully backward compatible with existing UMTS and GSM/GPRS networks. It contains two variants EC20 Mini PCIe-A and EC20 Mini PCIe-E, which makes it backward-compatible with existing EDGE and GSM/ GPRS networks to ensure that it can connect even in remote areas devoid of 4G or 3G coverage.

EC20 Mini PCIe supports Rx diversity which allows the end-device to be equipped with two distinct cellular antennas improving the quality and reliability of the wireless connectivity. Leveraging the Multiple-input multiple-output (MIMO) technology, its antennas at each end of the communications circuit are combined to minimize errors and optimize data speed. It also combines high-speed wireless connectivity with embedded multi-constellation high-sensitivity positioning GPS+GLONASS receiver.

A rich set of Internet protocols, industry-standard interfaces and abundant functionalities (USB drivers for Windows XP, Windows Vista, Windows 7, Windows 8/8.1, Linux, Android/eCall) extend the applicability of the module to a wide range of M2M applications such as CPE, router, data card, rugged tablet, automotive, security and industry PDA.


Key Benefits

- Worldwide LTE and UMTS/HSPA+ and GSM/GPRS/EDGE coverage
- Standard form factor ideal for manufacturers to easily integrate wireless connectivity into their devices
- MIMO technology meets demands for data rate and link reliability in modern wireless communication systems
- GNSS receiver available for applications requiring fast and accurate fixes in any environments
- Reference designs, evaluation tools and timely technical support minimize design-in time and development efforts

Quectel EC20

Mini PCIe

Multi-mode LTE Module



General Features

Frequency Bands	EC20-E Mini PCIe FDD LTE:B1/B3/B5/B7/B8/B20 UMTS:B1/B5/B8 GSM:850/900/1800/1900MHz
	EC20-A Mini PCIe FDD LTE:B2/B4/B5/B12/B17 UMTS:B2/B4/B5 GSM:850/1900MHz
LTE Version	EC20-C Mini PCIe FDD LTE:B1/B3/B8 TDD LTE:B38/B39/B40/B41 TDSCDMA:B34/B39 UMTS:B1/B8 GSM:900/1800MHz
	3GPP E-UTRA Release 9
Bandwidth	1.4/3/5/10/15/20MHz
Antenna	DL MIMO 2x2, supports Rx-diversity, GNSS
Supply Voltage Range	3.0V~ 3.6V, 3.3V Typ.
Operation Temperature	-40 °C ~ +80 °C
Dimensions	51.0mm×30.0mm×4.9mm
Weight	Approx. 9.8g
Control via AT commands	3GPP TS27.007 and enhanced AT Commands

Specifications

Data	LTE	LTE-FDD Max 100Mbps (DL) Max 50Mbps (UL)
	DC-HSPA+	Max 42Mbps(DL) Max 5.76Mbps(UL)
	UMTS	Max 384Kbps (DL) Max 384Kbps(UL)
	EDGE	Max 236.8Kbps(DL) Max 236.8Kbps
	GPRS	Max 85.6Kbps(DL) Max 85.6Kbps(UL)
Voice	Speech Codec Modes	HR,FR,EFR,AMR,AMR-WB
	Echo Arithmetic	Echo Cancellation Noise Reduction
eCall*		Accident, Emergency Services
VoLTE*		Digital Audio and VoLTE(Voice over LTE) (Optional)
Protocols*		TCP/UDP/PPP/FTP*/HTTP*/SMTP*/MMS*/SSL*

Special Features

Drivers	USB Serial	Windows XP, Windows Vista, Windows 7, Windows 8/8.1, Windows CE5.0*/6.0*/7.0*, Linux 2.6 or later, Android 2.3/4.0/4.2/4.4
	RIL	Windows CE6.0*, Windows Mobile 6.1*/6.5*, Android 2.3/4.0/4.2/4.4
	NIDS	Windows XP, Windows Vista, Windows 7, Windows 8, Windows CE5.0*/6.0*/7.0*
DFOTA		Firmware updated via the air
Firmware Update		Firmware Update via USB
GNSS		GPS/GLONASS (Optional)

Electrical Characteristics

Output Power	Class 3 (23dBm ±2dB) for LTE Class 3 (24dBm +1/-3dB) for UMTS Class E2 (27dBm ±3dB) for EDGE 850/900MHz Class E2 (26dBm ±3dB) for EDGE 1800/1900MHz Class 4 (33dBm ±2dB) for GSM 850/900MHz Class 1 (30dBm ±2dB) for GSM 1800/1900MHz
Consumption	5.5mA@Sleep.Type
Sensitivity	FDD B1: -97dBm(20M) FDD B2: -96dBm(20M) FDD B3: -96dBm(20M) FDD B4: -96dBm(20M) FDD B5: -99dBm(10M) FDD B7: -97dBm(20M) FDD B8: -98dBm(10M) FDD B12: -99dBm(20M) FDD B17: -99dBm(20M) FDD B20: -96dBm(20M) TDD B38: -94dBm(20M) TDD B39: -94dBm(20M) TDD B40: -94dBm(20M) TDD B41: -93.5dBm(20M) WCDMA B1: -110dBm WCDMA B2: -111dBm WCDMA B4: -111dBm WCDMA B5: -112dBm WCDMA B8: -111dBm TDSCDMA B34: -110dbm TDSCDMA B39: -110dbm GSM 850: -111dBm GSM 900: -110dBm GSM 1800: -109dBm GSM 1900: -109dBm

Interfaces

USB 2.0 Device	High Speed, 480Mbps Device Interface, Full Speed (12Mbps) Compliant
PCM	×1,Digital Audio through PCM Interface (Optional)
USIM	1.8V/3V
LED_WWAN#	Network Status
W_DISABLE#	Disable RF Function
UART	×1UART
PERST#	Reset Pin

Certification

Approval	CCC/CE/NAL/TA/KC*/SKT*/NCC*/ICASA*
-----------------	------------------------------------

* Under development